



https://www.xboat.uk/375-BENETEAU_FIRST-38S5.html



Main datas

Builder : Beneteau

Year : 1990

Length: 11,70

Draft minimum: 1,90

Hull: Monohull

Subtype:

Architect:

Material: GRP

Beam: 3,70

keel: Fixed Keel

Engines

Model:

Montage : In Board (IB)

Power Unit. (CV): 28

Fuel capacity: 110

Hours: 2650

Brand: Volvo Penta

Fuel : Diesel Engine(s) : 1

Drive : Shaft drive

Facilities

Sailor Cabin : 0

WC : Sailor Helm : No Double Cabin: 2

Head: 1 Berth: 6 Flybridge: No

Technical Details

Beneteau First 38S5

The Beneteau First 38S5 is a high-performance and elegant cruising sailboat, designed to offer a perfect balance between comfort and performance. This boat is ideal for sailors looking for a reliable and versatile vessel, capable of sailing both at sea and in inland waters.

Main Characteristics:

- Length overall: 11.58 m -
- Beam: 3.72 m -- Draft: 2.10 m -
- Displacement: 6,500 kg -
- Sail area (upwind): 70 m² -
- Sail area (downwind): 110 m² -
- Architect: Finot-Conq -
- Construction: Polyester hull reinforced with fiberglass -
- Water tank capacity: 200 liters -
- Fuel tank capacity: 100 liters -
- Engine: Yanmar 3YM30, 29 hp -

Desired Characteristics:

- Comfort: Spacious interior with 2 double cabins and 1 single cabin, equipped kitchen, and complete bathroom. -
- Performance: Good sea keeping and excellent maneuverability thanks to its marine rigging and modern navigation equipment. -
- Safety: Robust construction and high-quality safety equipment. -
- Versatility: Suitable for coastal cruising and long passages. -

The Beneteau First 38S5 is an ideal choice for sailing enthusiasts who want a reliable, high-performance, and comfortable boat for their nautical adventures.

Limitation of liability: XBOAT assumes no responsibility for the information provided in this technical data sheet, which has been sourced from the internet and has not been verified. This information is non-contractual and does not, in any way, bind XBOAT.

Médias











































































